

Finishing

GLAZETITE

High Quality Transparent Paint

**General Properties:**

- **GLAZETITE** is an emulsion synthetic resin, used as a gloss coat over matt paints.
- It can be used as a primer prior to paints after 50% dilution with water,
- Transparent paint that is slightly milky.
- Anti dust paint, gives a gloss surface.
- Has an excellent adhesion to substrate.
- Has excellent washability.

Uses:

- Finish glossy coat over emulsion matt paints.
- Primer over gypsum plasters or partitions, to strengthen the top layer before painting.
- Primer before high quality emulsion paints after dilution 50% with water.
- Can be used as a sealer to prevent carbonation & corrosion to:
 - Brick & stone walls.
 - Cement and concrete surfaces
 - Fiber panels.
 - Gypsum partitions.

Application:

1. Be sure that substrate is clean & free from all kinds of foreign materials.
2. Mix **GLAZETITE** in the container well before application.
GLAZETITE can be diluted with water up to 50%.
3. Apply **GLAZETITE** using a roller or a brush.
4. Clean tools immediately after application using water.

Note:

- The temperature of substrate should not exceed 30°C during application & it is recommended to damp the surface using water, especially in summer.
- **GLAZETITE** can be modified to be fungicide & biocide according to client's requirement. The brand name of the product is (**GLAZETITE F**).

Technical Data:

Binder	: Synthetic resins.
Anti fungus	: Fungicide.
Color	: Milky color.
Consumption	: 1 kg covers 6-12 m ² one coat depending on the surface condition.
Environment	: Friendly.
Shelf Life	: 12 months in closed container and away from sunlight, heat and humidity.

Environment: - Boots, rubber gloves, dust masks, and safety goggles.
- Refer to MATERIAL SAFETY DATA SHEETS (MSDS)

For more information please contact our technical department

Head Office: 21 Takseem El Awkaf – EL Sawah Sq. Cairo – Egypt
Tel: 002 / 02 24535678 - 24535679 Fax: 002 / 02 24538986
Web site: www.yasmomiser.com E-mail: yasmo@yasmomiser.com