

**General Properties:**

- **GRIFCOAT** is a ready mix paste product, formulated to provide decorative irregular **talon** scratches.
- Consists of selected mineral aggregates.
- Excellent adhesion.
- Excellent wash ability and high resistance to weathering.
- Non-sag mortar, high work ability and non-sag mortar.
- Supplied with different color.

**Uses:**

- Facades.
- Staircases.
- Decorative internal or external purposes.
- **GRIFCOAT** can be applied on all kinds of plaster, cement, stone and brick.

**Application:**

1. Clean substrate & remove any loose aggregates or foreign materials.
2. Mix **GRIFCOAT** well in container before application.
3. **GRIFCOAT** can be diluted with water if necessary.
4. Using stainless steel trowel apply the **GRIFCOAT** to the surface with a thickness about 2 mm.
5. Press gently using a plastic or wooden trowel vertically or horizontally or circular to obtain the required talon texture.
6. Clean tools immediately after application using water.

**Note:** The temperature of substrate should not exceed 30° C during application & it is recommended to damp the surface using water, especially in summer.

**Technical Data:**

<b>Binder</b>	: Synthetic resins.
<b>Adhesion</b>	: 1.5 N / mm <sup>2</sup> to concrete surface.
<b>Anti Fungus</b>	: Fungicide.
<b>Dilution</b>	: Water if necessary.
<b>Consumption</b>	: 3 – 4 kg/m <sup>2</sup> depending on the roughness & leveling of substrate.
<b>Environment</b>	: Friendly.
<b>Shelf Life</b>	: 12 months in closed container and away from sunlight, heat and humidity.

**Environment:** - Boots, rubber gloves, dust masks, and safety goggles.  
- Refer to MATERIAL SAFETY DATA SHEETS (MSDS)

**For more information please contact our technical department**

Head Office: 21 Takseem El Awkaf – EL Sawah Sq. Cairo – Egypt  
Tel: 002 / 02 24535678 - 24535679 Fax: 002 / 02 24538986  
Web site: [www.yasmomiser.com](http://www.yasmomiser.com) E-mail: [yasmo@yasmomiser.com](mailto:yasmo@yasmomiser.com)