

**General Properties:**

- **ACRYGLAZE** is a special solvent base acrylic paint formulated for high gloss transparent and colored finishing.
- Good elasticity thus recommended for applying on different vertical and horizontal substrata.
- Quick drying.
- High washability.
- High adhesion on different substrata.
- Suitable for both interior & exterior applications.

Uses:

- Decorative works.
- Finishing coat for all kind of wood.
- Paint to cement substrata specially subjected to corrosion and water.
- Paint to metal surfaces.

Application:

1. Clean substrate & ensure it is free of any foreign materials.
2. Mix **ACRYGLAZE** well in container before painting.
3. Apply the first coat using brush or spraying machine, **ACRYGLAZE** can be diluted till 20 % by its solvent.
4. The second day, apply the second or third coat if required using the same way (one coat daily).
5. Clean tools directly after application using Thinner.

Technical Data:

Bonding Agent	: Pure acrylic.
Dilution	: Solvent XX .
Consumption	: 0 – 6 m / 1 kg / one coat.
Ultra Violet Resistance	: non-yellowing.
Alcohol Resistance	: Excellent.
Shelf Life	: 12 months in closed containers away from direct sun light and humidity.

Environment: - Boots, rubber gloves, dust masks, and safety goggles.
- Refer to SAFETY MATERIAL DATA SHEETS (MSDS)

For more information please contact our technical department

Head Office: 21 Takseem El Awkaf – EL Sawah Sq. Cairo – Egypt
Tel: 002 / 02 24030678 – 24030679 Fax: 002 / 02 24038986
Web site: www.yasmomiser.com E-mail: yasmo@yasmomiser.com