



General Properties:

- **CRETEREP ٣٠** is two components ready mix repairing mortar, used for repairing cement substrata.
- Has maximum aggregate size ٠.٣ mm.
- Comp. (A) is a liquid & Comp. (B) is a powder.
- Is formulated to give high workability when using it as a fine paste material.
- Can be applied to the vertical, inclined & soffits surfaces.
- Has high water retention. To give excellent workability.

Uses:

- Cosmetic repair to cement substrata.
- As paste mortar prior to paints especially in facades & external finishing.
- **CRETEREP ٣٠** is the ideal putty prior to the epoxy paint.

Application:

١. Clean substrate before application & remove all loose particles.
٢. Substrate should be wet before application.
٣. Mix comp. A (liquid) well in a container before use & pour in a wide vessel.
٤. Add comp. B (powder) to the liquid & mix the mortar.
٥. Apply **CRETEREP ٣٠** with a suitable tool.
٦. Clean tools immediately after application using water.

Technical Data:

Binder	: Hydraulic & synthetic resins.
Water Retention	: High.
Constancy Volume	: Constant DIN ١١٦٤.
Sagging	: Non-sag mortar.
Density	: ١.٨٠ gm / cm ^٣ .
First Setting	: ٤٥ min at ٢٥°C.
Dilution	: Water, if necessary.
Admixture	: ASTM C ٤٩٤-٧١.
Shelf Life	: ١٢ months in closed containers away from direct sun light, heat and humidity.

- Environment:**
- **CRETEREP ٣٠** is non toxic and suitable for potable water structures.
 - Boots, rubber gloves, dust masks, and safety goggles.
 - Refer to MATERIAL SAFETY DATA SHEETS (MSDS).

For more information please contact our technical department

Head Office: ٢١ Takseem El Awkaf – EL Sawah Sq. Cairo – Egypt
 Tel: ٠٠٢ / ٠٢ ٢٤٥٣٥٦٧٨ – ٢٤٥٣٥٦٧٩ Fax: ٠٠٢ / ٠٢ ٢٤٥٣٨٩٨٦
 Web site: www.yasmomiser.com E-mail: yasmo@yasmomiser.com