

**General Properties:**

- **DURACOAT** is a special modified alkyd paint formulated for painting platforms, footpath, deck, curbstones.
- Semi-glossy texture.
- Rapid setting time.
- Easy in application.
- Based on styrenated alkyd.

Application:

١. Clean substrate well from dust, grease, salt or foreign materials.
٢. Mix **DURACOAT** well in container before application.
٣. Use a brush to apply the first coat.
٤. **DURACOAT** can be diluted using **SOLVENT M.S.** if necessary.
٥. The second coat can be applied after one hour.
٦. Clean tools immediately after application using solvent.

Technical Data:

Bonding Agent	: Special modified solvent based resin.
Specific Gravity	: ١.٣٨ kg/liter.
First Setting	: ١٠ min.
Dilution	: Solvent M S.
Shelf Life	: ١٢ in closed container away from direct sunlight, heat and humidity.

- Environment:**
- Boots, rubber gloves, dust masks, and safety goggles.
 - Refer to MATERIAL SAFETY DATA SHEETS (MSDS)

For more information please contact our technical department

Head Office: ٢١ Takseem El Awkaf – EL Sawah Sq. Cairo – Egypt
Tel: ٠٠٢ / ٠٢ ٢٤٥٣٥٦٧٨ – ٢٤٥٣٥٦٧٩ Fax: ٠٠٢ / ٠٢ ٢٤٥٣٨٩٨٦
Web site: www.yasmomiser.com E-mail: yasmo@yasmomiser.com