

**General Properties:**

- **FLESSCOAT** is ready to use emulsion paint formulated with special minerals to be applied by roller, has a please uniform rough texture coat.
- Has a several textures according to the kind of roller used.
- Excellent adhesion.
- Can be applied directly without pasting the substrata over smooth render and fair face concrete.
- Has the breathing property.
- Has high hiding power even in one coat.
- Helps in absorbing & breaking down sound waves to a great extend.
- Resists severe weathering.

Uses:

- Mainly Exterior paints.
- Halls and staircases.
- Theaters and cinemas.
- Decorative purposes.
- **FLESSCOAT** can be applied on all kinds of renders, plasters, asbestos, wood, stone, brick, fair face concrete.

Application:

1. Clean substrate and remove any foreign materials.
2. It is recommended to damp substrate before application especially in summer.
3. Mix **FLESSCOAT** well in container before application.
4. If the substrate is high absorbent it is recommended to apply a primer coat **FLESSCOAT** diluted till 15% with water.
5. Using a roller apply the first coat **FLESSCOAT**.
6. The second day, apply the second coat, if required.
7. Clean tools immediately using water.

Note:

- The temperature of substrate should not exceed 30°C during application & it is recommended to damp the surface using water, especially in summer.
- **FLESSCOAT F** can be modified to be fungicide & biocide according to client's requirement. The brand name of the product is (**FLESSCOAT F**).

Technical Data:

Binder	: Synthetic resins.
Anti Fungus	: Fungicide.
U.V Resistance	: Non-yellowing.
Dilution	: Water if required.
Consumption	: 0.8 – 1.2 kg/m ² (one coat depends on roughness of substrate).
Density	: 1.67 kg / liter.
Environment	: Friendly.
Shelf Life	: 12 months in closed container and away from sunlight, heat and humidity.

Environment: - Boots, rubber gloves, dust masks, and safety goggles.
- Refer to MATERIAL SAFETY DATA SHEETS (MSDS)

For more information please contact our technical department

Head Office: 21 Takseem El Awkaf – EL Sawah Sq. Cairo – Egypt
Tel: 002 / 02 24535678 - 24535679 Fax: 002 / 02 24538986
Web site: www.yasmomiser.com E-mail: yasmo@yasmomiser.com