

Finishing

## FLESSCRETE

Decorative Proofing Paint



### General Properties:

- **FLESSCRETE** is a colored cement base coat consists of two components.
- Component (A) is liquid and component (B) is powder made of selected aggregate and hydraulic binder.
- Decorative texture coat helps in water proofing finish.
- Non-sag product.
- Characterized by breathing property.
- Excellent adhesion to substrate.
- Has minimum shrinkage.
- Environmentally Friendly.

### Uses:

- The function of **FLESSCRETE** is to work as a final proofing textured finish coat (white and colored).
- **FLESSCRETE** is formulated to be applied over damp substrate reinforced concrete, plain concrete, brick work or cement render such as:
  - Basement.
  - Substrates exposed to permanent water.
  - External surfaces of water tanks and swimming pools.
  - Lower parts of walls especially those surrounded with damp soil.

### Application:

1. Clean the substrate from foreign material & loose particles.
2. Old paint should be removed.
3. Damp the substrate with water.
4. Pour the liquid (component A) in a suitable container and add the powder (component B) to liquid slowly & stir, till you reach a homogenous mixture recommended to use low speed mechanical admixture.
5. Leave the mixture for 5 minutes & remix again till all lumps disappear.
6. Using a roller apply two coats one coat daily.
7. Clean tools directly after application using water.

**Note:** The temperature of substrate should not exceed 30°C during application & it is recommended to damp the surface using water, especially in summer.

### Technical Data:

<b>Binder</b>	: Synthetic resins + hydraulic bond.
<b>Mixing</b>	: Component (A) liquid 5 kg (plastic jerkin). : Component (B) Powder 15 kg (double plastic bags).
<b>Adhesion To Concrete</b>	: 1.8 N / mm <sup>2</sup> .
<b>Consumption</b>	: 1.2 kg covers 1m <sup>2</sup> one coat.
<b>Anti Fungus</b>	: Fungicide.
<b>Dilution</b>	: With water if required.
<b>Pot Life</b>	: 60 minutes in 25°C.
<b>Shelf Life</b>	: 12 months in closed container and away from sunlight, heat and humidity.

**Environment:** - Boots, rubber gloves, dust masks, and safety goggles.  
- Refer to MATERIAL SAFETY DATA SHEETS (MSDS)

**For more information please contact our technical department**

Head Office: 21 Takseem El Awkaf – EL Sawah Sq. Cairo – Egypt  
 Tel: 002 / 02 24535678 - 24535679 Fax: 002 / 02 24538986  
 Web site: [www.yasmomisr.com](http://www.yasmomisr.com) E-mail: [yasmo@yasmomisr.com](mailto:yasmo@yasmomisr.com)