
Finishing

FLESSPRAY





General Properties:

- FLESSPRAY is ready mix emulsion paint, formulated to be applied by air spray machine, it has a please uniform rough texture coat.
- Excellent adhesion.
- Can be applied directly over smooth render, concrete, without pasting the substrate.
- Has the breathing property.
- Has high hiding power even in one coat.
- Helps to a great extend to absorb & break down sound waves.
- Resists severe weathering.

Uses:

- Mainly exterior paints.
- Staircases and Halls.
- Theaters & Cinemas.
- Decorative purposes.
- Can be applied on all kinds of renders, plasters, asbestos, stone, wood, brick, cement substrata, fair faces concrete.

Application:

- 1. Be sure that substrate is clean & free from any foreign materials.
- 7. If the surface needs repairing (recommended CRETEREP **) especially in facades.
- T. Mix the **FLESSPRAY** in container well before application.
- £. FLESSPRAY can be thinned with water if necessary.
- An air pressure-spraying machine is the suitable one for application.
- Clean tools immediately after application using water.

Note: The temperature of substrate should not exceed "· 'C during application & it is recommended to damp the surface using water, especially in summer.

The above product can be modified to be fungicide & biocide according to client's requirement. The brand name of any product shall be marked with letter "F"i.e. (FLESSPRAY F).

Technical Data:

Binder : Synthetic resins. U.V. Resistance : Non-yellowing.

Consumption : \lambda epend on the roughness of the surface.

Anti Fungus : Fungicide.

Dilution: Water if necessary.

Environment: Friendly.

Shelf Life : \footnote{\text{ months in closed containers away from sun light, heat}

and humidity.

Environment: - Boots, rubber gloves, dust masks, and safety goggles.

- Refer to MATERIAL SAFETY DATA SHEETS (MSDS)