

Finishing

GRANULIC

Colored Decorative Coat



General Properties:

- **GRANULIC** is ready mix decorative colored paste, pigmented with special high standard colors.
- Combined with blended aggregates to provide a decorative shaded coat.
- Non-sag plaster coat.
- Easy for application.
- Excellent adhesion to cement substrata.
- High resistance to ultra violet.
- Consists of natural blended aggregates.

Uses:

- Facades.
- Staircases.
- Decorative uses.

Application:

1. Clean surface; be sure it is free from all foreign materials.
2. Any cracks or scratches should be repaired before application (recommended **CRETEREP**).
3. Mix the **GRANULIC** well in the container before application.
4. **GRANULIC** can be thinned with water if necessary.
5. Using a stainless Steel trowel apply **GRANULIC** to substrate.
6. Average thickness approximately 2mm - 3mm depending on the roughness of the surface.
7. Clean tools using water directly after application.

Note: The temperature of substrate should not exceed 30°C during application & it is recommended to damp the surface using water, especially in summer.

Technical Data:

Binder	: Synthetic resins.
Anti Fungus	: Fungicide.
U.V. Resistance	: Non-yellowing.
Dilution	: Water if necessary.
Consumption	: 3 – 4 kg / m ² .
Environmental	: friendly.
Shelf Life	: 12 months in closed container and away from sunlight, heat and humidity.

Environment: - Boots, rubber gloves, dust masks, and safety goggles.
- Refer to MATERIAL SAFETY DATA SHEETS (MSDS)

For more information please contact our technical department

Head Office: 21 Takseem El Awkaf – EL Sawah Sq. Cairo – Egypt
Tel: 002 / 02 24030678 – 24030679 Fax: 002 / 02 24038986
Web site: www.yasmomiser.com E-mail: yasmo@yasmomiser.com