

**General Properties:**

- **GRANULITE** is a ready mix paste mortar, ready to be applied directly from the container.
- Consists of natural blended colored stones.
- Gives the effect of natural color, which will not be affected by ultraviolet.
- Non-sag mortar.
- Easy for application.
- Excellent adhesion to substrate.
- Excellent wash ability.

**Uses:**

- External facades.
- Staircases.
- Decorative uses.

**Application:**

1. Ensure that substrate is clean & free from foreign materials.
2. All cracks & scratches should be repaired before application (Recommended **CRETEREP**).
3. Mix the material well in the container, before application.
4. **GRANULITE** can be thinned with water if necessary.
5. Apply **GRANULITE** using stainless steel trowel.
6. Average thickness is approximately 2mm - 3mm & depends on surface leveling.

**Note:** The temperature of substrate during application should be less than 30°C & it is recommended to damp the surface before application especially in summer.

**Technical Data:**

<b>Binder</b>	: Synthetic resins.
<b>Anti Fungus</b>	: Fungicide.
<b>U.V. Resistance</b>	: Non-yellowing.
<b>Density</b>	: 1.6 kg / liter.
<b>Dilution</b>	: Water if necessary.
<b>Consumption</b>	: 3 – 4 kg/m <sup>2</sup> .
<b>Environment</b>	: Friendly.
<b>Shelf Life</b>	: 12 months in closed container and away from sunlight, heat and humidity.

**Environment:** - Boots, rubber gloves, dust masks, and safety goggles.  
- Refer to MATERIAL SAFETY DATA SHEETS (MSDS)

**For more information please contact our technical department**

Head Office: 21 Takseem El Awkaf – EL Sawah Sq. Cairo – Egypt  
Tel: 002 / 02 24030678 – 24030679 Fax: 002 / 02 24038986  
Web site: [www.yasmomiser.com](http://www.yasmomiser.com) E-mail: [yasmo@yasmomiser.com](mailto:yasmo@yasmomiser.com)