Finishing

GRIFCOAT L



Decorative Plaster Coat

General Properties:

- GRIFCOAT L is a ready mix paste product, formulated to provide decorative irregular talon scratches.
- Consists of selected mineral aggregates.
- Excellent adhesion.
- Excellent wash ability and high resistance to weathering.
- Non-sag mortar, high work ability and non-sag mortar.
- Supplied with different color.

Uses:

- Facades.
- Staircases.
- Decorative internal or external purposes.
- GRIFCOAT L can be applied on all kinds of plaster, cement, stone and brick.

Application:

- 1. Clean substrate & remove any loose aggregates or foreign materials.
- Y. Mix **GRIFCOAT** L well in container before application.
- T. GRIFCOAT L can be diluted with water if necessary.
- ٤. Using stainless steel trowel apply the **GRIFCOAT L** to the surface with a thickness about ^۲ mm.
- Press gently using a plastic or wooden trowel vertically or horizontally or circular to obtain the required talon texture.
- 7. Clean tools immediately after application using water.

<u>Note</u>: The temperature of substrate should not exceed $^{r, \circ}$ C during application & it is recommended to damp the surface using water, especially in summer.

Technical Data:

Binder : Synthetic resins.

Adhesion : •. Y N / mm² to concrete surface.

Anti Fungus: Fungicide.

Dilution: Water if necessary.

Consumption: $^{r} - ^{\xi} \text{ kg/m}^{\tau}$ depending on the roughness & leveling of

substrate.

Environment: Friendly.

Shelf Life : \tag{Y} months in closed container and away from sunlight, heat

and humidity.

Environment: - Boots, rubber gloves, dust masks, and safety goggles.

- Refer to MATERIAL SAFETY DATA SHEETS (MSDS)

For more information please contact our technical department