Finishing

GRIFMENT



Decorative Plaster Coat

General Properties:

- GRIFMENT is cement base, dry product, formulated to provide decorative irregular talon scratches.
- Consists of selected aggregates just add water before application.
- Excellent adhesion.
- Excellent washability.
- Non-sag mortar.
- Characterized by it hardness & durability.
- Suitable pot life after mixing.
- Can be supplied with different colors.

Uses:

- Facades.
- Staircases.
- Decorative internal or external purposes.
- **GRIFMENT** can be applied on all kinds of plaster, cement, stone and brick works.

Application:

- 1. Clean substrate & remove loose aggregates or foreign materials.
- 7. Wet the substrate well directly before application.
- T. Put water in a suitable container (about \o'\tilde{\circ} of the weight of the **GRIFMENT**) then add **GRIFMENT** powder with continuous mixing.
- Using stainless steel trowel apply the GRIFMENT to the surface with a thickness according to the size of aggregates present in GRIFMENT.
- Press gently using the trowel vertically or horizontally or circular to obtain the required texture.
- Clean tools immediately after application using water.

<u>Note</u>: The temperature of substrate should not exceed "· C during application & it is recommended to damp the surface using water, especially in summer.

Technical Data:

Binder : Hydraulic binder.

State : Dry powder.

Consumption : \land \text{kg / m} \text{ / mm thickness.} **Pot Life** : \(\frac{\psi}{\psi} \text{ minutes after mixing.}\)

Adhesion Strength : > \ N / mm on cement substrate (Din\\\\0000\\)) (EN \\\\\)).

Abrasion : \infty mg (\infty cycle - \infty mg).

Environment : Friendly.

Shelf Life : ۱۲ months in closed container and away from sunlight, heat

and humidity.

Environment: - Boots, rubber gloves, dust masks, and safety goggles.

- Refer to MATERIAL SAFETY DATA SHEETS (MSDS)

For more information please contact our technical department