

Finishing

## GUMCOAT V

Egg Shell Gloss Emulsion Paint



### General Properties:

- **GUMCOAT V** is egg shell gloss emulsion paint that provides fine texture.
- Resists moisture and weathering.
- Resists ultraviolet, non-yellowing and non-pollutant.
- Very easy to clean.
- Excellent elasticity & washability.
- Excellent hiding power.
- High cohesion & excellent adhesion.

### Uses:

- Used in exterior & interior paints.
- Painting corridors, bathrooms, kitchens, and laundries.
- Decorative purposes.

### Type of Substrate:

- All kinds of plaster, render, cement, wood, steel, fiber, gypsum panels & old paints.

### Application:

1. Ensure that substrate is clean & free from foreign materials.
2. Paste the substrate for smoothing, recommended **FILLCOAT**.
3. Apply undercoat of a matt paint, recommended **ZODIAC / INCOAT**.
4. Mix **GUMCOAT V** well in the container before application.
5. Apply **GUMCOAT V** using a roller (wool or spongy). Two coats are enough.  
**GUMCOAT V** can be diluted up to 10% with water for the first coat.
6. Close container tightly after application.
7. Clean tools immediately after application using water.

### Note:

- The temperature of substrate should not exceed 30<sup>0</sup>C during application & it is recommended to damp the surface using water, especially in summer.
- **GUMCOAT V** can be modified to be fungicide & biocide according to client's requirement. The brand name of the product is (**GUMCOAT F**).

### Technical Data:

<b>Bond</b>	: Passed sample test no. A (no squares removed).
<b>Wash ability</b>	: > 6000 cycles (after 7 days)
<b>Drying Time</b>	: <b>Surface:</b> 10 min at 30°C. <b>Hard:</b> 30 min at 30°C.
<b>Scrub ability</b>	: Passed.
<b>Water &amp; Alkaline resistance</b>	: Passed (14 days submerged in water).
<b>Elasticity</b>	: Passed (on rod 0.9mm).
<b>Density</b>	: 1.30 Kg/liter.
<b>Resistance to Ultraviolet</b>	: No yellowing happened after 360 hour exposure.
<b>Fungicide</b>	: Anti fungus.
<b>Dilution</b>	: Water if necessary.
<b>Consumption</b>	: 7 -9 m <sup>2</sup> / 1 kg.
<b>Coverage Film Thickness</b>	: 50 micron.
<b>Environment</b>	: Friendly.
<b>Shelf Life</b>	: 12 months in closed container and away from sunlight, heat and humidity.

- Environment:**
- Boots, rubber gloves, dust masks, and safety goggles.
  - Refer to MATERIAL SAFETY DATA SHEETS (MSDS)

**For more information please contact our technical department**

Head Office: 21 Takseem El Awkaf – EL Sawah Sq. Cairo – Egypt  
 Tel: 002 / 02 24535678 - 24535679 Fax: 002 / 02 24538986  
 Web site: [www.yasmomiser.com](http://www.yasmomiser.com) E-mail: [yasmo@yasmomiser.com](mailto:yasmo@yasmomiser.com)