

Finishing

GYPCOAT ٢٠٠

Modified Gypsum



General Properties:

- **GYPCOAT ٢٠٠** is modified ready mix gypsum, combined with selected graded aggregates, to achieve higher thickness without cracks.
- Can be applied with thickness from ٥mm up to ٥٠mm.
- Excellent adhesion to substrate.
- Can be applied by machine gun.
- Setting time range between ٤٠-٦٠ min.

Substrate:

- All cement substrate.
- All kinds of brick work.
- All kinds of stones.

Uses:

- Plaster coat instead of cement render can be applied till thickness ٥٠ mm one shot.

Application:

١. Clean substrate well.
٢. Wet substrate with water especially in summer.
٣. Pour water in a wide vessel then add **GYPCOAT ٢٠٠** gradually to the water.
٤. Mix well manually or by a mechanical mixer.
٥. Apply **GYPCOAT ٢٠٠** using a stainless steel trowel with a thickness up to ٥٠ mm.

Technical Data:

Color	: Off white
Specification	: Complies with BS ١١٩١ part ٢.s - ASTM C٢٨
Compressive Strength	: ٧٥ Kg/cm ^٢
Thickness	: ٥ mm to ٥٠ mm as one coat
Consumption	: ١ ton covers ١٣٠-١٤٠ m ^٢ ٥mm thickness
Water Ratio	: ٢٦ % from Gypcoat ٢٠٠ powder
Environment	: Friendly
Setting Time	: ٤٠ - ٦٠ minutes
Shelf Life	: ١٢ months in closed container and away from sunlight, heat and humidity.

- Environment:**
- Boots, rubber gloves, dust masks, and safety goggles.
 - Refer to MATERIAL SAFETY DATA SHEETS (MSDS)

For more information please contact our technical department

Head Office: ٢١ Takseem El Awkaf – EL Sawah Sq. Cairo – Egypt
 Tel: ٠٠٢ / ٠٢ ٢٤٥٣٥٦٧٨ – ٢٤٥٣٥٦٧٩ Fax: ٠٠٢ / ٠٢ ٢٤٥٣٨٩٨٦
 Web site: www.yasmomiser.com E-mail: yasmo@yasmomiser.com