

INTERCOAT

One Shot Emulsion Paint



General Properties:

- **INTERCOAT** is an emulsion paint used to be applied directly using a roller; one coat is enough.
- Matt textured coat.
- Several textures can be obtained according to the roller used.
- Can be used for interior & exterior surfaces.
- Is relatively flexible thus resists hair cracks.
- No need to paste the substrate.
- Saves time & labor cost.

Application:

1. Clean surface from foreign materials.
2. Be sure that holes are filled, recommended **CRETEREP**.
3. **INTERCOAT** can be applied on all kinds of plaster, render, cement, gypsum, wood, fiber panels...etc
4. Mix **INTERCOAT** well in the container before application.
INTERCOAT can be thinned with water if necessary according to the final finish needed.
5. Using a wool or spongy roller apply **INTERCOAT**, only one coat is enough.
6. Close container tightly after application.
7. Clean tools immediately after application using water.

Note:

- The temperature of substrate should not exceed 30°C during application & it is recommended to damp the porous surfaces using water, especially in summer.
- **INTERCOAT** can be produced to be fungicide & biocide according to client's requirement

The brand name of the product is **INTERCOAT F**.

Technical Data:

Binder	: Synthetic resins.
U.V resistance:	Non-yellowing.
Anti fungus	: Fungicide.
Dilution	: Water if necessary.
Density	: 1.65 kg/liter.
Consumption	: 1kg -1.2kg / m ² depending on roughness of substrate & kind of texture needed.
Environment	: Friendly.
Shelf Life	: 12 months in closed container and away from sunlight, heat and humidity.

Environment: - Boots, rubber gloves, dust masks, and safety goggles.
- Refer to MATERIAL SAFETY DATA SHEETS (MSDS)

For more information please contact our technical department

Head Office: 21 Takseem El Awkaf – EL Sawah Sq. Cairo – Egypt
Tel: 002 / 02 24535678 - 24535679 Fax: 002 / 02 24538986
Web site: www.yasmomiser.com E-mail: yasmo@yasmomiser.com