

**General Properties:**

- **LAQMOON MT** is a pigmented paint based on alkyd resin.
- Gives matt smooth paint.

Uses:

- Paint for all wooden, metallic, cement and gypsum substrata.

Application:

1. Clean surfaces well from dust, grease, salt or any foreign materials.
2. Sanding the surface well.
3. Apply suitable primer recommended "**WASHSTEEL**", if required.
4. Mix **LAQMOON MT** well in container before application.
5. **LAQMOON MT** can be diluted by its **SOLVENT M.S** if necessary ..
6. Apply **LAQMOON MT** by brush or spray gun.
7. Second day apply the second coat if necessary.
8. Clean tools immediately after application using solvent.
9. Close the container well after application.

Technical Data:

Bonding Agent	: Modified Alkyd resin.
Density	: 1.6 kg/liter.
Dilution	: SOLVENT MS if necessary.
Consumption	: 0-7 m ² /kg / one coat.
Abrasion Resistance	: Excellent.
Water Resistance	: Excellent.
Shelf Life	: 12 months in closed container and away from sunlight, heat and humidity.

Environment:

- Boots, rubber gloves, dust masks, and safety goggles.
- Refer to MATERIAL SAFETY DATA SHEETS (MSDS).

For more information please contact our technical department

Head Office: ٢١ Takseem El Awkaf – EL Sawah Sq. Cairo – Egypt
Tel: ٠٠٢ / ٠٢ ٢٤٥٣٥٦٧٨ – ٢٤٥٣٥٦٧٩ Fax: ٠٠٢ / ٠٢ ٢٤٥٣٨٩٨٦
Web site: www.yasmomiser.com E-mail: yasmo@yasmomiser.com