

**General Properties:**

- **LAQMOON** is a white or pigmented paint based on alkyd resin.
- Durable and stable colors, non-yellowing.
- Excellent sheen.
- Gives smooth finishing.

Uses:

- Paint for all wooden, metallic, cement and gypsum substrata.

Application:

1. Clean surfaces well from dust, grease, salt or any foreign materials.
2. Sanding the surface well.
3. Apply suitable primer recommended "**WASHSTEEL**", if required.
4. Mix **LAQMOON** well in container before application.
5. **LAQMOON** can be diluted by its **SOLVENT M.S** if necessary.
6. Apply **LAQMOON** by brush or spray gun.
7. Second day apply the second coat if necessary.
8. Clean tools immediately after application using solvent.
9. Close the container well after application.

Technical Data:

Bonding Agent	: Modified Alkyd resin.
Density	: 1.16 kg/liter.
Dilution	: SOLVENT MS if necessary.
Consumption	: 7 - 10 m ² /kg / one coat.
Abrasion Resistance	: Excellent.
Water Resistance	: Excellent.
Shelf Life	: 12 months in closed container and away from sunlight, heat and humidity.

Environment: - Boots, rubber gloves, dust masks, and safety goggles.
- Refer to MATERIAL SAFETY DATA SHEETS (MSDS)

For more information please contact our technical department

Head Office: 21 Takseem El Awkaf – EL Sawah Sq. Cairo – Egypt
Tel: 002 / 02 24535678 - 24535679 Fax: 002 / 02 24538986
Web site: www.yasmomiser.com E-mail: yasmo@yasmomiser.com