

Finishing

MISR SEAL

Sealer and primer for all kind of emulsion paints

**General Properties:**

- **Misrseal** is a special type of sealer that have a very small molecular weight that can penetrate through voids of substrate
- Capable to minimize the absorption of water through the voids.
- Distinguish for bonding loss particles in substrate and strengthen the weak substrate
- Has high bond to substrata like : gypsum , cement , wood , poor paints or any porous substrate
- Penetrate through the voids of substrate to create high mechanical bond
- Can penetrates through voids up to 10mm according to the type of substrate

Uses:

- Primer to wood, render, plaster, concrete, gypsum, or any porous substrate to accept top layers.
- Fixing defected coatings & gypsum layers.
- Priming on reinforced concrete surfaces specially at seashore constructions prevents carbonation to cement & oxidation to steel.

Applications:

1. Clean the substrate from any foreign materials
2. Be sure to stir the product in the container before use
3. Apply MISRSEAL with roller or brush , one coat is enough for the up coats
4. Clean tools with water right after finishing application

Technical Data:

Binder	: Synthetic resins with very low molecular weight.
Consumption	: 6 – 9 m ² /kg according to substrate roughness and porosity .
Density	: 1.35 gm/cm ³
Dilution	: With water till 10 % .
Environment	: Friendly.
Shelf Life	: 12 months in closed container and away from sunlight, heat and humidity.

Environment:

- Boots, rubber gloves, dust masks, and safety goggles.
- Refer to MATERIAL SAFETY DATA SHEETS (MSDS)

END OF TECHNICAL DATA

For more information please contact our technical department

Head Office : 21 Takseem El Awkaf – EL Sawah Sq. Cairo – Egypt
 Tel : 002 / 02 24535678 - 24535679 Fax : 002 / 02 24538986
 Web site : www.yasmomiser.com E-mail: yasmo@yasmomiser.com



28437/A



28437/B



28437/C