

Finishing

RUBCOAT

Decorative Elastic Paint

**General Properties:**

- **RUBCOAT** is a decorative elastic coat; its thickness can reach up to 3 mm by applying several coats.
- Gives different textures according to the used roller.
- Easy in application. One coat could be enough.
- High elasticity.
- Very easy to clean.
- Has the power of echo absorption.
- Excellent washability.
- Has high cohesion and adhesion.
- Has a matt aspect, with vertical or circular scratches depending on the application process.

Uses:

- Echo absorption coating:
It's specially manufactured to dampen unwanted voices and vibrations due to its very high elasticity and flexibility; it converts sound producing resonance low-grade heat instead of noise.
- Decorative uses, hospitals, corridors, halls, theaters & cinemas.
- Works as proofing membrane to wood inclined roof systems.
- In courts, with thickness 2-3 mms as a finish coat over sound substrate. It can be reinforced with fiberglass sheets.

Application:

١. Clean the surface well & fill gaps, recommended **CRETEREP**.
٢. Primer is essential, recommended **VERSASEAL**.
٣. **RUBCOAT** can be applied without pasting the surface.
٤. Mix **RUBCOAT** well in container before application.
٥. **RUBCOAT** can be thinned using water if necessary.
٦. Using a roller apply several coats to get the required thickness.
٧. First setting needs 2-4 hours / coat (depends on the layer thickness).
٨. Clean tools immediately after application using water.

Note:

- The temperature of substrate should not exceed 30 °C during application & it is recommended to damp the surface using water, especially in summer.
- **RUBCOAT** can be modified to be fungicide & biocide according to client's requirement. The brand name of the product is (**RUBCOAT F**).

Technical Data:

Binder	: Synthetic resins.
Wash ability	: 4000 cycles (after 7 days).
Density	: 1.0 Kg/liter.
U.V Resistance	: Non-yellowing.
Anti Fungus	: Fungicide.
Elongation	: 80 %.
Dilution	: Water if necessary.
Consumption	: 1 kg covers 2-3 m ² one coat.
Environment	: Friendly.
Shelf Life	: 12 months in closed container and away from sunlight, heat and humidity.

Environment:

- Boots, rubber gloves, dust masks, and safety goggles.
- Refer to MATERIAL SAFETY DATA SHEETS (MSDS).

For more information please contact our technical department

Head Office: ٢١ Takseem El Awkaf – EL Sawah Sq. Cairo – Egypt
 Tel: ٠٠٢ / ٠٢ ٢٤٥٣٥٦٧٨ – ٢٤٥٣٥٦٧٩ Fax: ٠٠٢ / ٠٢ ٢٤٥٣٨٩٨٦
 Web site: www.yasmomiser.com E-mail: yasmo@yasmomiser.com