

Finishing

STAMLEASE

Release Agent For Stamped Concrete

**General Properties:**

- **STAMLEASE** is a ready mix dry powder, consists of a special treated powder to prevent adhesion of concrete to stamp tool.
- Its fundamental objective is to give a non tacky release coat between the stamp and the colored concrete before stamping.
- Colored release powder that is sprayed directly over the layer of **STAMPTOP** to give decorative shadows with different **STAMPTOP** colors

Uses:

- As a release layer over wet fresh concrete after spraying it with **STAMPTOP** (due to its pigmentation power it can be used to get a combined colored stamped concrete).

Application:

1. After casting the concrete , level the surface manually using trowel (before the first setting and just as the concrete becomes dull, i.e. no excessive water exists)
2. Spray the **STAMPTOP** directly over the surface. (consumption ~ 3 - 4 kg / m²)
3. Spray the colored **STAMLEASE** over the surface **STAMPTOP**. (Consumption ~ 200 – 250 gm/ m²)
4. Use stamp tool to create the decorative texture as required.

Technical Data:

Consumption : 200 – 250 gm/m²

Packaging : 10 kg

Shelf Life : 12 months in closed container and away from sunlight, heat and humidity.

- Environment:**
- Boots, rubber gloves, dust masks, and safety goggles.
 - Refer to MATERIAL SAFETY DATA SHEETS (MSDS)

END OF TECHNICAL DAT

For more information please contact our technical department

Head Office : 21 Takseem El Awkaf – EL Sawah Sq. Cairo – Egypt
 Tel : 002 / 02 24535678 - 24535679 Fax : 002 / 02 24538986
 Web site : www.yasmomisr.com E-mail: yasmo@yasmomisr.com



28437/A

28437/B

28437/C