

Mortars

STAMPTOP

Colored Surface Hardener Stamped Concrete

**General Properties:**

- STAMPTOP is ready mix colored dry powder consists of selected modified minerals.
- The fundamental objective is to give a hard decorative colored layer to the fresh concrete before stamping.
- It is an inorganic colored powder which can be used before applying STAMLEASE (release agent) to get a decorative Stamped concrete with several colors.

Uses:

- Used to build up a layer over wet fresh concrete to give hard and tough colored layer.
- Due to its pigmentation, it is generally used in decorative and stamped concrete.

Application:

1. Cast the concrete and level the surface manually using required tool. (Before the first setting and just as the concrete become dull i.e. No excessive water).
2. Spray the STAMPTOP directly over the top surface. (consumption 3 - 4 kg / m²).
3. Trowel and finish the surface manually.
4. Spray the colored STAMLEASE over the surface STAMPTOP. (consumption 200 – 250 gm/ m²).
5. Use the stamp tool manually to create the required decorative texture.
6. On the second day wash and clean the concrete with water to get rid of any loose powder.
7. Apply the top coat of stamped concrete using acrylic, epoxy or any other suitable sealer.

Technical Data:

Consumption : 3 – 4 kg/m² .

Shelf Life : 12 months in closed container and away from sunlight, heat and humidity.

- Environment:**
- Boots, rubber gloves, dust masks, and safety goggles.
 - Refer to MATERIAL SAFETY DATA SHEETS (MSDS)

END OF TECHNICAL DATA

For more information please contact our technical department

Head Office : 21 Takeem El Awkaf – EL Sawah Sq. Cairo – Egypt

Tel : 002 / 02 24535678 - 24535679 Fax : 002 / 02 24538986

Web site : www.yasmomisr.com E-mail: yasmo@yasmomisr.com