

**General Properties:**

- **TIMBERTONE** is a special varnish formulated for painting all kinds of wood.
- Fast drying.
- Excellent bond to wood.
- High glossy varnish coat.
- Has a good scrub ability and abrasion resistance.
- Very easy in application.
- Very easy to be cleaned.

Application:

1. Ensure that all dust, oil, grease & foreign materials are cleaned.
2. Environment protection should be considered, wear eye goggles and be sure of good ventilation.
3. Using a brush or spraying machine apply the first coat **TIMBERTONE**, it can be diluted till 10% using its solvent. (**SOLVENT MS**).
4. The second day, apply the second coat that can be diluted 5%.
5. The third coat (if required) can be applied on the third day.

Technical Data:

Initial Drying	: From 2-5 hours.
Density	: 0.9 kg/liter.
Water Resistance	: Excellent.
Abrasion	: Excellent.
Consumption	: 10-12 m ² /kg / one coat.
Shelf Life	: 12 months in closed container and away from sunlight, heat and humidity.

- Environment:**
- Boots, rubber gloves, dust masks, and safety goggles.
 - Refer to MATERIAL SAFETY DATA SHEETS (MSDS)

For more information please contact our technical department

Head Office: 21 Takseem El Awkaf – EL Sawah Sq. Cairo – Egypt
Tel: 002 / 02 240306778 – 240306779 Fax: 002 / 02 24038986
Web site: www.yasmomiser.com E-mail: yasmo@yasmomiser.com