

**General Properties:**

- **WASHSTEEL** is steel primer with red iron oxide as filling material.
- Has special filling to resist different weather conditions.
- Has the advantage of resisting salts and moisture.
- Is used directly on steel & wood surfaces prior to painting.
- Excellent washability.

Application:

1. Clean the surface well from rust, grease, salts or any foreign materials.
2. Sandblast can be used, if necessary; be sure that sand is totally free of moisture.
3. Wear gloves & goggles before application.
4. Priming with **WASHSTEEL** should be applied within max. four hours of preparing the surface.
5. **WASHSTEEL** can be diluted with **SOLVENT MS**.
6. Priming can be applied in one coat or two coats as required.
 - * The second coat can be applied on the second day.
7. Brush or spray can be used for application.
8. Clean tools immediately after application using solvent.

Technical Data:

Bonding agent	: Synthetic resins.
Color	: Red.
Density	: 1.38 kg /lit.
Solvent	: SOLVENT MS till 20%.
Coverage	: 6-8 m ² / kg one coat.
Shelf life	: 12 months in closed container and away from sunlight, heat and humidity.

- Environment:**
- Boots, rubber gloves, dust masks, and safety goggles.
 - Refer to MATERIAL SAFETY DATA SHEETS (MSDS)

For more information please contact our technical department

Head Office: 21 Takseem El Awkaf – EL Sawah Sq. Cairo – Egypt
Tel: 002 / 02 24030678 – 24030679 Fax: 002 / 02 24038986
Web site: www.yasmomiser.com E-mail: yasmo@yasmomiser.com