

**General Properties:**

- **WOODSIEVE** is a polymeric adhesive specially formulated, to adhere porous to porous materials.
- Excellent adhesion.
- Ideal for adhering wood and wooden substrata to each other.
- Adhesive for pottery.
- Wallpaper adhesive, when diluted 90% with water.
- Adhesive for wood to brick, gypsum or cement substrate.

**Uses:**

- Used as an adhesive for porous to porous materials.

**Application:**

1. Smooth & clean both substrate & material to be adhered.
2. Mix **WOODSIEVE** in container before application.
3. Using a brush apply a layer of the adhesive to both substrate.
4. Adhere the material to the surface and press on it.
5. After 12 hours you get excellent adhesion.
6. Close container tightly at end of work.
7. Clean tools after application using water.

**Technical Data:**

<b>Binder</b>	: Synthetic resins.
<b>Consistency</b>	: Milky viscous liquid.
<b>Bond Strength</b>	: 9 kg/cm <sup>2</sup> .
<b>Dilution</b>	: Water if necessary.
<b>Anti-Fungus</b>	: Fungicide.
<b>First Setting</b>	: 30 minutes.
<b>Final Setting</b>	: 7 days.
<b>Shelf Life</b>	: 12 months in closed container away from sunlight, heat and humidity.

**Environment:**

- Boots, rubber gloves, dust masks, and safety goggles.
- Refer to MATERIAL SAFETY DATA SHEETS (MSDS)

**For more information please contact our technical department**

Head Office: 21 Takseem El Awkaf – EL Sawah Sq. Cairo – Egypt  
Tel: 002 / 02 240306778 – 240306779 Fax: 002 / 02 24038986  
Web site: [www.yasmomiser.com](http://www.yasmomiser.com) E-mail: [yasmo@yasmomiser.com](mailto:yasmo@yasmomiser.com)